



5F Annex Dragon Pearl Plaza
 2123 Pudong Avenue
 Shanghai 200135 - P.R. CHINA
 Tél. : +86 21 68 55 50 32
 Fax : +86 21 68 55 50 33
 E-mail : ctcshanghai@ctcgroupe.com

TEST REPORT

Report No.: S170405004_1

21 April 2017

APPLICANT: 太仓市顺林针织品有限公司 (C34448)
 江苏太仓市沙溪镇周泾路158号

Date of receipt : 19 Apr. 2017
 Testing period : 21 Apr. 2017
 : 21 Apr. 2017

Buyer: ---

Test(s) requested : ---
 Service : EXPRESS
 Brand / Section : ---
 Season : ---
 End use : ---
 Factory name : ---
 Factory code : ---

For CE Marking : Yes

Previous report : ---
 Product category : ---
 Product type : ---
 Test stage : FIRST TEST
 Supplier name : ---
 Exported to : ---

1. Conclusion:

	<u>Tests description</u>	<u>Conformity</u>
1	Abrasion resistance : 2016 : EN 388 : 2016	Level 1
2	Tear strength resistance: 2016 : EN 388 : 2016	Level 3

Pass: requirements met Fail: requirements not met None: no requirement for this test N/A: not applicable

Approved by

Henry YAN
 Laboratory Supervisor

TEST REPORT

Report No.: S170405004_1

21 April 2017

APPLICANT: 太仓市顺林针织品有限公司 (C34448)

2. Sample(s) description assigned by laboratory:

<u>Size</u>	<u>Analyzed product</u>	<u>Description</u>	<u>Sample information</u>
	GLOVE	palm	



170405004

TEST REPORT

Report No.: S170405004_1

21 April 2017

APPLICANT: 太仓市顺林针织品有限公司 (C34448)

3. GLOVE/

palm

	Method	Client Requirement	Unit	Result	Conformity
Tear strength resistance: 2016 Tear strength Tear strength (2) Tear strength (3) Tear strength (4) Performance level	EN 388 : 2016		N N N N	63 66 >75 >75 3	
Abrasion resistance : 2016 Deviation from the test method used consumables - abrasive used consumables - adhesive Number of cycles at the hole detection Number of cycles at the hole detection (2) Number of cycles at the hole detection (3) Number of cycles at the hole detection (4) Performance level	EN 388 : 2016			NO Klingspor PL31B Grit 180 3M 200 100 100 200 1	

END OF TEST REPORT

Table of Performance Level for Glove

Test Item	Performance Level					
	0 ^{##}	1	2	3	4	5
Abrasion Resistance (EN 388) Number of cycles (minimum)	<100	100	500	2000	8000	---
Tear Resistance (EN 388) Force (N) (minimum)	<10	10	25	50	75	---

Performance level 0 means the glove falls below the minimum performance level for the given individual hazard